


power transmission optibelt RED POWER 3



Il Cuscinetto srl - www.ilcuscinetto.it - info@ilcuscinetto.it

PERFECT FOR HIGH PERFORMANCE **DRIVES**

COMPACT: HIGH PERFORMANCE IN CONFINED SPACES


Reconfiguring systems using optibelt RED POWER 3 V-belts allows space-saving and cost-effective designs to be created with fewer belts and an associated reduction in axial and bearing loads.





HIGHER PERFORMANCE

Up to 50% higher power transmission capacity compared to conventional standard V-belts



PERFECT POWER TRANSMISSION




HIGH TEMPERATURE RESISTANCE

Resistant from -30°C to +100°C



TEMPERATURE RESISTANT: STRONG IN HEAT AND COLD

optibelt RED POWER 3 V-belts ensure consistent power transmission within a temperature range of -30 °C to +100 °C.



EXACTLY THE NOMINAL SIZE

SET CONSTANT WITHOUT MEASURING: ALWAYS THE NOMINAL SIZE

Optibelt S=C Plus is the epitome of perfect power transmission. The tight length tolerances are made possible by modern production methods, the long-standing expertise of professionals, and the use of consistently high quality raw materials.



S=C PLUS

V-belts, set constant without measuring

OPTIBELT ROTARY-VULCANIZATION - ORV

S=C Plus tolerances and optimized dynamic belt performance are ensured by the special Optibelt Rotary-Vulcanization.

PERFORMING UP TO THE LIMIT

The **optibelt RED POWER 3** achieves up to 50% higher power capability than conventional V-belts. This means that fewer belts are required for power transmission and sustainable cost savings are possible by reducing the pulley sizes. If the same number of belts are used, pulleys with a smaller diameter can be employed.



PERFECT FOR HIGH PERFORMANCE APPLICATIONS

COVER FABRIC

Rubber-coated fabric cover for high wear resistance, special fabric construction for increased flexibility

TENSION CORD


Particularly low stretch polyester cord

TOP LAYER

High-quality mixture made of polychloroprene with transverse fibres

BASE LAYER

Core mixture made of polychloroprene with transverse fibres for increased transverse rigidity and improved cord support



IDEAL IN MECHANICAL ENGINEERING

- Compressors
- Fans
- Pumps
- Mixers
- Presses
- Stone crushers
- Highly loaded drives


PROFILES/SIZES V-BELTS

SPZ	1170–18 000 mm
SPA	1170-18 000 mm
SPB	1170-12 000 mm
SPC	1900-21 000 mm
3V/9N	460-7080 in
5V/15N	460-4720 in
8V/25N	820-7080 in

PROFILES/SIZES KRAFTBANDS

2240-10000 mm
2240-10000 mm
880-3930 in
880-3930 in
820-8260 in

Further dimensions available on request



V-GROOVED PULLEYS


SPZ/SPC pulleys for finished bore or optibelt taper bush available, special pulleys on request




optibelt RED POWER 3

Construction in cross section









Corveyer Allee 15 37671 Höxter GERMANY **T** +49 5271 621 **F** +49 5271 976200 **E** info@optibelt.com



PT/PROSPEKT RED POWER 3/EN/0520

